



3" C-BOND HYBRID SERIES

HYBRID DIAMOND TOOLING


Increase efficiency with the industry's most effective and economical hybrid series! The SASE® Hybrid Wet C-Bond Series boasts a new and improved formula that includes an exclusive, proprietary copper matrix resulting in up to 300% increase in tooling life and easy and effective transitioning between metal and resin bond steps.



HOL.300600

30 GRIT (LIME)


This tool is designed for wet operation and can be used to remove cure and seal off new concrete and/or be the initial starting point to expose salt and pepper aggregate. It can also be used to remove 25 grit metal scratches.



HOL.300601

50 GRIT (GREY)


This tool is designed for wet operation and can be used to remove cure and seal off of new concrete and/or be the initial starting point to expose salt and pepper aggregate. It can also be used to remove 40 grit metal scratches.



HOL.300602

100 GRIT (BLACK)

This tool is designed for wet operation and can be used to remove thin cure and seal off of new concrete and or be the initial starting point to expose little to no aggregate (cream finish). It can also be used to remove 80 grit metal scratches and removal step after a grout coat application.



HOL.300603

200 GRIT (BLUE)

This tool is designed for wet operation and can be used to remove 100 grit hybrid and/or 150 grit metal scratches.



HOL.300604

400 GRIT (RED)

This tool is designed for wet operation and can be used to remove 200 grit hybrid scratches and in some cases, remove 100 grit hybrid scratches.



HOL.300605

800 GRIT (WHITE)

Designed to follow up the scratch pattern of the 400g C-bond wet and preparing the floor for a final polish 1500g dry for maximum shine and clarity.

Products manufactured and marketed by SASE® Company are protected by patents issued or pending in the United States and other countries. SASE® Company reserves the right to change the specifications referred to in this literature at any time, without prior notice. © 2024 SASE® Company, Inc. All rights reserved.

1-800-522-2606
SASEcompany.com

