

METAL BOND AQUA SERIES

METAL DIAMOND TOOLING

The new SASE® Aqua Series Metal Bond Diamond Tooling is tailored for wet grinding. This new matrix bond maximizes productivity and value in wet grinding applications. Designed to work on most concrete regardless of hardness. Perfect solution for the removal of medium to thin coatings, cure and seals, primers and glue residue.



HOL.502636QCS

25 GRIT (DOUBLE SEG.)

Ideal for wet grinding. Optimized for maximum productivity at a great value. Works on most concrete hardness applications.



HOL.502637QCS

40 GRIT (DOUBLE SEG.)

Ideal for wet grinding. Optimized for maximum productivity at a great value. Works on most concrete hardness applications.



HOL.502638QCS

80 GRIT (DOUBLE SEG.)

Ideal for wet grinding. Optimized for maximum productivity at a great value. Works on most concrete hardness applications.



HOL.502639QCS

150 GRIT (DOUBLE SEG.)

Ideal for wet grinding. Optimized for maximum productivity at a great value. Works on most concrete hardness applications.

Products manufactured and marketed by SASE® Company are protected by patents issued or pending in the United States and other countries. SASE® Company reserves the right to change the specifications referred to in this literature at any time, without prior notice. © 2024 SASE® Company, Inc. All rights reserved.

1-800-522-2606
SASEcompany.com

