


# WULF® CLAW REMOVAL TOOLS

## REMOVAL & PREPARATION TOOLING

Maximize removal rates without excessive damage to the floor. The new Wulf® Claw from SASE® bridges the gap between PCD's and metal diamond tooling, without adding step to the process. Removal of glues, thinsets, water proofing membranes, epoxies, floats and patches without destroying the underlying substrate.



HOL.200515

### WULF® IRON CLAW REMOVAL TOOL - GOLD


Gold is for Hard to Medium Concrete. The Wulf® Claw bridges the gap between PCD's and metal diamond tooling, without adding steps to the process. Removal of glues, thinsets, water proofing membranes, epoxies, floats and patches without destroying the underlying substrate.



HOL.200516

### WULF® STEEL CLAW REMOVAL TOOL - BLACK

Black is for Medium to Soft Concrete. The Wulf® Claw bridges the gap between PCD's and metal diamond tooling, without adding steps to the process. Removal of glues, thinsets, water proofing membranes, epoxies, floats and patches without destroying the underlying substrate.



HOL.200517

### WULF® IRON CLAW REMOVAL TOOL - BLUE

Blue is for Medium to Hard Concrete. The Wulf® Claw bridges the gap between PCD's and metal diamond tooling, without adding steps to the process. Removal of glues, thinsets, water proofing membranes, epoxies, floats and patches without destroying the underlying substrate.



HOL.200518

### WULF® STEEL CLAW REMOVAL TOOL - YELLOW

Yellow is for the Hardest Concrete. The Wulf® Claw bridges the gap between PCD's and metal diamond tooling, without adding steps to the process. Removal of glues, thinsets, water proofing membranes, epoxies, floats and patches without destroying the underlying substrate.

Products manufactured and marketed by SASE® Company are protected by patents issued or pending in the United States and other countries. SASE® Company reserves the right to change the specifications referred to in this literature at any time, without prior notice. © 2024 SASE® Company, Inc. All rights reserved.

1-800-522-2606  
SASEcompany.com

