

WULF® SERIES PCD RINGS

REMOVAL & PREPARATION TOOLING

The SASE® Wulf® Series is a complete range of coatings removal and concrete floor preparation tooling. The PCD Rings allow for fast and effective removal of thin to thick coatings.



B-SIDE DIRECTIONAL TOOLING

B-side Directional Tooling are Counter Clockwise and can be used with Propane-powered machines.

DRY USE



REMOVAL



PREP



HOL.201014 (A)

PCD 11" / 270MM RING W/ WEAR BAR - (A)

For fast, effective thin to medium mil coatings removal without damaging the concrete surface. Diamond wear bar controls depth of cut. 0-2 mm medium mil



HOL.201012 (A)

PCD GOLD 11" / 270MM RING - (A)

For fast, effective very thick mil coatings removal. Tears through elastic or rubberized membranes and compounds. >3 mm very thick mil



HOL.201015 (B)

PCD 11" / 270MM RING W/ WEAR BAR - (B)

For fast, effective thin to medium mil coatings removal without damaging the concrete surface. Diamond wear bar controls depth of cut. 0-2 mm medium mil



HOL.201013 (B)

PCD GOLD 11" / 270MM RING - (B)

For fast, effective very thick mil coatings removal. Tears through elastic or rubberized membranes and compounds. >3 mm very thick mil



HOL.201016 (A)

FULL PCD 270MM PLATE W/ ARROW WEAR BAR SILVER - (A)

For fast, effective thin to medium mil coatings removal without damaging the concrete surface. Diamond wear bar controls depth of cut. 0-2 mm medium mil



HOL.201017 (B)

FULL PCD 270MM PLATE W/ ARROW WEAR BAR SILVER - (B)

For fast, effective very thick mil coatings removal. Tears through elastic or rubberized membranes and compounds. >3 mm very thick mil



NB.13.216

PCD RING MOUNTING SCREWS (FOR EXTRA SAFETY)

For use when mounting PCD 11" rings and bush hammers to floor grinder heads for extra safety.

Products manufactured and marketed by SASE® Company are protected by patents issued or pending in the United States and other countries. SASE® Company reserves the right to change the specifications referred to in this literature at any time, without prior notice. © 2024 SASE® Company, Inc. All rights reserved.

1-800-522-2606

SASEcompany.com

