

WULF® SERIES PCD'S

REMOVAL & PREPARATION TOOLING

The SASE® Wulf® Series is a complete range of coatings removal and concrete floor preparation tooling. The series includes tooling that can handle thin to thick coatings above 3 mils.



B-SIDE DIRECTIONAL TOOLING

B-side Directional Tooling are Counter Clockwise and can be used with Propane-powered machines.

DRY USE



REMOVAL



PREP



HOL.200997QCS

PCD SPLIT DS

For fast, effective thin mil coatings removal. 0 - 1 mm thin mil



HOL.200512

PCD FULL ROUND W/ ARROW WEAR BAR - (A)

For fast, effective very thick mil coatings removal. Tears through elastic or rubberized membranes and compounds. >3 mm very thick mil



HOL.200996QCS

PCD SPLIT SS


For fast, effective thin mil coatings removal. 0 - 1 mm thin mil



HOL.200513

PCD FULL ROUND W/ ARROW WEAR BAR - (B)

For fast, effective very thick mil coatings removal. Tears through elastic or rubberized membranes and compounds. >3 mm very thick mil



HOL.200510 (A)

PCD WEAR BAR - (A VERSION)

For fast, effective thin to medium mil coatings removal without damaging the concrete surface. Diamond wear bar controls depth of cut. 0-2 mm medium mil



HOL.200993 (A)

PCD 1/4 ROUND ON ARROW DS - (A)

For fast, effective very thick mil coatings removal. Tears through elastic or rubberized membranes and compounds. >3 mm very thick mil



HOL.200511 (B)

PCD WEAR BAR - (B VERSION)

For fast, effective thin to medium mil coatings removal without damaging the concrete surface. Diamond wear bar controls depth of cut. 0-2 mm medium mil



HOL.200994 (B)

PCD 1/4 ROUND ON ARROW SS - (B)

For fast, effective very thick mil coatings removal. Tears through elastic or rubberized membranes and compounds. >3 mm very thick mil

Products manufactured and marketed by SASE® Company are protected by patents issued or pending in the United States and other countries. SASE® Company reserves the right to change the specifications referred to in this literature at any time, without prior notice. © 2024 SASE® Company, Inc. All rights reserved.

1-800-522-2606
SASEcompany.com

